NASA Technical Memorandum 101630

THERMAL AND ORBITAL ANALYSIS OF EARTH MONITORING SUN-SYNCHRONOUS SPACE EXPERIMENTS

Brian D. Killough

(NASA-TM-101630) THERMAL AND ORBITAL ANALYSIS OF EARTH MONITORING SUN-SYNCHRONOUS SPACE EXPERIMENTS (NASA) 16 p CSCL 228

N90-25168

Unclas G3/18 0290749

May 1990



	· · · · · · · · · · · · · · · · · · ·
	•

THERMAL AND ORBITAL ANALYSIS OF EARTH MONITORING SUN-SYNCHRONOUS SPACE EXPERIMENTS

Brian D. Killough NASA Langley Research Center Hampton, Virginia

INTRODUCTION

This report presents a method for generating all the orbital parameters needed for the thermal analysis of spacecraft in Earth monitoring Sun-synchronous orbits. The level of complexity is suitable for initial planning of missions. The mechanics of Sun-synchronous orbits and their impact on the thermal design of space experiments is discussed in detail. A \underline{S} un-synchronous \underline{O} rbit \underline{A} nalysis \underline{P} rogram (SOAP) was developed to calculate the orbital parameters necessary for a complete thermal analysis. An example case run with this program is discussed.

ANALYSIS OF SUN-SYNCHRONOUS ORBITS

An overview of Sun-synchronous orbits is presented here with particular emphasis on their application to Earth-monitoring missions. Additional analysis of Sun-synchronous orbits can be found in reference 1. Sun-synchronous orbit is one whose right ascension of ascending node precesses at a rate which matches the average apparent rotation rate of the Sun about the Earth. This type of orbit is desirable for many types of Earth-monitoring missions because it allows for near-global coverage of the Earth's surface and atmosphere and repetitive latitude-longitude observations at near-constant conditions of solar illumination. Also of special significance for Earth observing satellites, are the times during which the Sun is rising or setting on the Earth's horizon, as viewed from the spacecraft. During sunset and sunrise it is possible to obtain vertical profiles of many different atmospheric constituents which attenuate the Sun's radiation. A spacecraft in Sun-synchronous orbit, with a typical low Beta angle (angle between the solar vector and the orbit plane), will continue to experience a sunrise and sunset every revolution, for as long as the orbit is maintained. In the case of a purely Earth monitoring experiment, atmospheric data can be recorded over the same area under the same lighting conditions at a constant time increment.

Sun-synchronous orbits are retrograde, that is, the velocity component of the spacecraft in the equatorial plane opposes the rotational motion of the Earth. Thus, the orbit inclination (angle between the orbit plane and equatorial plane) will always be greater than 90 degrees. For circular orbits, the inclination is only a function of the orbit altitude. The variation of Sun-synchronous orbit inclination for circular orbits up to an altitude of 1600 kilometers is shown in Figure 1.

¹The Beta angle defined in this paper will always refer to the angle between the orbit plane and the Sun. Other publications often use the complement to this angle.

Another special characteristic of a Sun-synchronous orbit is that the orbit repetition factor (Q) is identical to the number of orbit revolutions in one day. Therefore, assuming a circular orbit, any Sun-synchronous orbit has the special property that its ground track will repeat precisely at intervals of a whole number of days. Table 1 shows the number of orbital revolutions per day as a function of orbit inclination or orbit altitude. This quantity Q is important for defining the longitude and latitude ground coverage of an Earth monitoring satellite. For example, an integer value for Q means that a particular ground track will be duplicated the next day. If Q includes a fraction, such as one-fifth, then the initial longitude coverage will be duplicated every five days. Therefore, long repeat cycles will allow for good longitude coverage, but poor repeat coverage. Similarly, short repeat cycles give good repetition, but poor longitude coverage (ref. 2).

It is necessary to note that, though a Sun-synchronous Earth monitoring orbit implies a fixed geometry with respect to the Sun, the solar radiation flux input is not necessarily fixed, but actually varies considerably. This is due to the satellite's path which crosses around the Earth and maintains a constant view of the Earth on one side. Though no single side of the satellite is fixed with respect to the Sun, there is often one side that receives a high average solar flux during an orbit. For example, if the satellite orbit plane is in line with the Sun, the satellite will receive direct solar radiation on its zenith side for the part of the orbit when the satellite is between the Earth and the Sun. As the satellite moves past the polar region it will go behind the Earth, thus being blocked from the Sun's radiation entirely. This type of orbit configuration can cause problems for optical experiments using nadir detectors with a horizon to horizon view. In this case, the nadir, or earth facing side of the experiment, will experience direct solar flux during sunrise and sunset as seen from the satellité as it passes around the Earth. The other extreme case occurs when the satellite orbit plane is perpendicular to the Sun. This will cause one side of the satellite to receive full solar flux. Similarly, the opposite side of the satellite would be facing deep space during the entire orbit.

As with any space experiment, the solar illumination or radiation flux input has a considerable impact on the thermal and mechanical design. Therefore, it is appropriate to discuss the orbital alignment with the Sun, specifically as it applies to an Earth monitoring Sun-synchronous experiment. In this case, the initial timing of the orbit is important, since it will determine the envelope of angles between the solar vector and the orbit plane. 'The initial timing of a Sun-synchronous orbit is often referred to as the "orbit time", which represents the longitudinal difference between the sun and the point where the spacecraft crosses the equator (15 degrees per hour). For example, if an orbit time of local clock noon is chosen, then the orbit plane would be closely in line with the Sun and the angle between the Sun and the orbit plane would be very small, even approaching zero at times. Each time the satellite passes the equator the local clock time at this crossing position on the Earth would be noon. Similarly, an orbit time six hours later would produce angles near 90 degrees and an envelope that generally includes larger angles. This type of orbit could create thermal problems since a particular side of the experiment would be facing the Sun at all times, providing the nadir side maintains a constant Earth view. In any event, the characteristics of a Sun-synchronous orbit have a direct effect on the design of a space experiment.

It is customary that the orbit time be expressed as either an ascending node or descending node. This describes the path of the satellite as it crosses the equator. In the case of an ascending node orbit, the satellite passes the equator traveling from South to North. Similarly, a descending node orbit crosses the equator traveling from North to South. Thus a 2:00 pm ascending node orbit is equivalent to a 2:00 am descending node orbit.

SUN-SYNCHRONOUS ORBIT ANALYSIS PROGRAM

A Sun-synchronous Orbit Analysis Program (SOAP), written in FORTRAN language, was created to calculate orbital parameters for an entire year for a fixed orbit altitude and orbit time. The source program has been written in the form of a subroutine, designed to be called from any other computer code. The subroutine and a sample calling program are supplied in Appendix A and an example output is presented in Appendix B. The input and output calling arguments, for the SOAP subroutine, are shown in Appendix C and the governing equations used to calculate orbital parameters are presented in Appendix D.

The program is valid for Sun-synchronous orbits with launch dates after 1950 including leap years. Inputs for the program include the year of the launch, experiment altitude and Sun-synchronous orbit time. Output data includes orbit inclination angle, time in hours for a complete orbit or revolution time, a set of data for the maximum and minimum Beta angle, and orbital data for the entire year including solar declination, right ascension of the Sun, and longitude of the ascending node. The orbital parameters calculated by this program are extremely tedious to do by hand and require repetitive calculations for every day of the year. Thus, this program provides an efficient method for determining all of the orbital parameters needed for a thermal radiation analysis.

It was stated previously that a Sun-synchronous orbit allowed for a fixed inclination angle and a fixed revolution time. All of the other parameters are a function of orbital position and the day of the year. A typical set of output data will contain a maximum and minimum Beta angle for the year of interest. Though the year and altitude have a small effect on the Beta angles, the Sun-synchronous orbit time has the largest effect on these angles and their corresponding magnitudes. For example, a 6:00 orbit produces a large variation in the Beta angle with the average angles being high, even approaching 90 degrees in some cases. An orbit time of 12:00 would produce the smallest variation in Beta angle and the maximum and minimum angles would The yearly variation in Beta angle is due to both be below 10 degrees. seasonal variation of the Earth's position with respect to the Sun. In the case where the orbit plane is inclined at a high angle with respect to the Sun (orbit times near noon), the Earth's seasonal tilt will create large variations in Beta angle. Similarly, when the orbit plane is closely aligned with the Sun (orbit times near 6:00), the Earth's tilt has little effect on the Beta angle. Figure 2 shows the variation in Beta angle for different Sun-synchronous orbit times. These results, calculated by the SOAP computer program, are for a fixed altitude and year.

 $^{^2}$ The source code can be acquired on either diskette or magnetic tape by contacting the author of this publication. Note, the author will not be responsible for any changes in the source code made by the user.

THERMAL ANALYSIS APPLICATION

A specific example case was chosen to illustrate the use of the Sun-synchronous Orbit Analysis Program (SOAP) in calculating the orbital fluxes incident on a Sun-synchronous space experiment. The example utilizes a radiation analysis program to predict heat fluxes on a cube for one complete orbit. Results from the orbital analysis program, described in the previous section, are used as input to this radiation program. An example orbit will be presented and the orbital heating data will be summarized.

The orbit chosen for this application was a 1:30 p.m. ascending node Sun-synchronous circular orbit with an altitude of 705 km and a launch date in 1998. Representative values for the solar constant, Earth infrared radiation and the Earth albedo were used. These values are commonly used by thermal analysts for spacecraft design. It was also assumed that the spacecraft surface was black, such that the emissivity and absorptivity were 1.0. This orbit data was used in the SOAP computer code to calculate pertinent orbit parameters required by the Thermal Radiation Analyzer System (TRASYS) program (ref.3). These parameters are summarized in Table 2. The TRASYS program was employed to define the incident infrared, solar and Earth albedo heat fluxes acting on a space experiment for one complete orbit. Thermal flux data were generated for one orbit on two distinct days of the year when the Sun's location, relative to the experiment, yields the highest and lowest Beta angles. These two days represent the highest and lowest average heat fluxes for the year. The ultraviolet (UV), which includes the solar and albedo fluxes, and the Earth infrared (IR) flux contributions are shown in Table 3. These heat fluxes can be used as the basis for further thermal analysis including sizing radiators or predicting instrument operating temperatures. Since these two sets of data contain the highest and lowest average heat fluxes for the year, the thermal analyst can be assured that all orbital heating fluxes will fall within these limits.

CONCLUSIONS

The fundamentals of an Earth monitoring Sun-synchronous orbit were presented. A Sun-synchronous Orbit Analysis Program (SOAP) was developed to calculate orbital parameters for an entire year. The output from this program provides the required input data for the TRASYS thermal radiation computer code, which in turn computes the infrared, solar and Earth albedo heat fluxes incident on a space experiment. Direct incident heat fluxes can be used as input to a generalized thermal analyzer program to size radiators and predict instrument operating temperatures. The SOAP computer code and the thermal analysis methodology presented in this paper should prove useful to the thermal engineer during the design phases of future Earth monitoring Sun-synchronous space experiments.




Figure 1. Sun-synchronous orbit inclination angle versus orbit altitude




Figure 2. Beta angle versus day of the year for various sun-synchronous orbit times

REPETITION FACTOR (Q)	ALTITUDE (KM)	INCLINATION ANGLE (DEG)
12	1684.6	102.94
12 1/8	1629.1	102.63
12 1/4	1574.4	102.33
12 1/2	1467.9	101.75
13	1265.3	100.71
13 1/8	1216.6	100.47
13 1/4	1168.7	100.24
13 1/2	1075.2	99.79
14	896.5	98.99
14 1/8	853.4	98.80
14 1/4	811.0	98.62
14 1/2	728.1	98.28
15	569.1	97.64
15 1/8	530.8	97.49
15 1/4	492.9	97.35
15 1/2	418.8	97.07
16	276.3	96.57

Table 1. Circular Sun-Synchronous Orbit Parameters for Specific Repetition Factors

PARAMETER	DATE	
	July 9, 1998	November 5, 1998
Days After January 1	190	309
Longitude of Ascending Node	130.77	248.07
Right Ascension of the Sun	108.19	220.10
Solar Declination	22.39	-15.60

Orbital Constants:

Orbit Altitude = 705 km

Sun-synchronous Orbit Time = 1:30 pm Ascending Node

Revolution Time = 1.65 hours

Eccentricity = 0.0

Thermal Analysis Constants:

Solar Constant = 1352 W/m*m

Earth Infrared Radiation = 236.6 W/m*m

Earth Albedo = 0.30

Incident Flux Properties:

Absorptivity = 1.0

Emissivity = 1.0

Table 2. TRASYS Input Parameters

St	ırface Flux [Data (W/m*	m) – July 9, 1998	B (Beta Ar	ngle = 17.28	3)	
Orbit Position (deg)	Flux Type	Velocity	Anti-Velocity	Sun	Anti-Sun	Nadir	Zenith
0	UV IR	0 55	0 55	0 53	0 53	0 1 9 5	0
30	UV IR	0 55	0 55	0 53	0 53	0 1 9 5	0
60	UV IR	0	0	0	0	0	0
90	UV	55 1154	55	53 387	53	195 586	0
120	IR UV	55 1309	55	53 396	53 4	195 2 4	74
	IR	55	55	53	53	195	0
150	UV IR	1141 55	40 55	437 53	44 53	174 195	711 0
180	UV IR	667 55	75 55	466 53	73 53	283 1 9 5	1157 0
210	UV IR	89	164 55	475	82 53	317 195	1293
240	UV	55 69	791	53 461	68	265	1083
270	IR UV	55 30	55 1207	53 428	53 35	195 143	583
290	IR UV	55 3	55 1308	53 400	53 8	195 39	0 152
	IR	55	55	53	53	195	0
323	UV IR	0 55	1155 55	387 53	0 53	586 195	0
350	UV IR	0 55	0 55	0 53	0 53	0 195	0
Su			n) – November 5				
0	UV	0	0	0	0	0	0
20	IR UV	55 0	55 0	53 0	53 0	195 0	0
47	IR UV	55 1031	55 0	53 648	53	195 587	0
,	IR	55	55	53	53	195	0
80	UV IR	1199 55	1 55	659 53	53	21 195	63 0
120	UV IR	930 55	49 55	707 53	48 53	198 195	810 0
150	UV IR	428 55	75	729 53	69 53	278 195	1135 0
170	UV	81	55 145	732	73	290	1185
210	IR UV	55 53	55 876	53 711	53 52	195 212	0 867
250	IR UV	55 3	55 1198	53 664	53 6	195 38	0 144
	IR	55	55	53	53	195	0
287	UV IR	0 5 5	1031 55	648 53	0 53	587 195	0
310	UV IR	0 55	0 55	0 53	0 53	0 195	0
340	UV	0	0	0	0	0	0
	IR I	55	55	53	53	195	0

Table 3. Experiment Heat Flux Data

Appendix A SOAP Computer Program Listing

```
Sun-Synchronous Orbit Analysis Program (SOAP)
       written in the form of a FORTRAN SUBROUTINE
       Written by: Brian Killough - NASA Langley Research Center
                                          Mail Stop 431
                                          Hampton, VA 23665 (804) 864-7047
       This program calculates all of the necessary orbital parameters
       for a sun-synchronous space experiment, input for the program includes the year, experiment altitude, and sun-synchronous orbit
       time. Output for the program includes the BETA angle (angle between the sun and the experiment orbit plane) for each day of
       the year, and the maximum and minimum BETA angles for that year. These maximum and minimum BETA angles are used to calculate
       orbital parameters such as: Julian Date, Days Relative to January
1, Solar Declination, Orbit inclination, Longitude of the Ascending
Node, Right Ascension of the Sun, and the Orbit Time. These
parameters can be used to run any radiation analysis program that
       calculates radiation fluxes over one orbit, on a given day.
      PROCEAM MAIN
    THIS IS AN EXAMPLE CALLING PROGRAM
      DIMENSION BETA(366), DECLI(366), LONGAS(366), RASSUN(366)
      DIMENSION MONTHS(2).DAYS(2).COUNTS(2)
      REAL BETA DECLI LONGAS RASSLIN
      REAL ALT, TLAUNCH, INCL, OTIME
      INTEGER LEAP. MONTHS, DAYS, COUNTS, YEAR
      CHARACTER 20 OUTFILE
     **CORACT (/, Sun-Synchronous Orbit Analysis Program (SOAP)",/,
     FORMAT(1X, 'Enter an output file name in SINGLE quotes: ')
      READ . OUTFILE
      OPEN(UNIT=2, FILE=OUTFILE)
      PRINT 30
      FORMAT(1X, 'Enter the Year:')
      READ . YEAR
      FORMAT(1X, 'Enter the Experiment Altitude (km):')
      PRINT SO
      FORMAT(IX, 'Enter the Sun-Synchronous Orbit Time:')
      PRINT 68
     FORMAT(IX, 'Example >> 13.5 (= 1:30 pm ascending Node)')
      READ . TLAUNCH
      CALL SOMPLYEAR, ALT, TLAUNCH, LEAP, MONTHS, DAYS, COUNTS, INCL, OTIME,
                BETA, DECLI, LONGAS, RASSUN, TERROR)
      IF ( IERROR .NE. 0 ) GO TO 1
     WEITE(2.60)
     FORMAT (1X, 'Sun-Synchronous Orbit Analysis Program (SOAP)')
     WRITE(2,100) YEAR
FORMAT (1X, Year of Launch = '.14)
    FORMAT (1X, 'Year of Launch = ',14)
WRITE(2,120) ALT
FORMAT (1X, 'Altitude (km) = ',F5.1)
WRITE(2,140) TLAUNCH
FORMAT (1X,' Sun-Synchronous Orbit Time = ',F5.2)
      WR | TE(2, 150)
     WRITE(2,160) INCL
FORMAT (1X, 'Orbit inclination angle,deg. = ',F5.2)
     WRITE(2,170) OTIME
FORMAT (1X, ' Orbit Time (hours) = ',F4.2)
     FORMAT (1X.
    180
    WRITE(2,190) BETA(COLATS(1))
FORMAT (IX, Maximum Beta Angle, deg. = ',F6.2)
WRITE(2,200) MONTHS(1),DAYS(1)
     FORMAT (1X, Date of Maximum Beta Angle + '.12.'/'.12)
    WRITE(2,210) COUNTS(1)
FORMAT (IX, Days Relative to January 1 = ',14)
    WRITE(2,220) DECLI(COUNTS(1))
FORMAT (1X, Solar Declination, deg. = ',F4.2)
      RITE(2,230) LONGAS(COUNTS(1))
     FORMAT (1X, Longitude of Ascending Node, deg. = ',F6-2)
     FORMAT (1x, ' Right Ascension of the Sun,deg. = ',F6.2'
     WEITE(2 250)
    MITE(2,260) BETA(COLNTS(2))
     FORMAT (1X ' minimum Beta Angle dec. w '.F6.2)
     WRITE(2, 278) MONTHS(2).DAYS(2)
```

FORMAT (1X. ' Date of minimum Seta Angle = '.12.'/'.12)

```
WRITE(2,200) COUNTS(2)
FORMAT (1X,* Days Relative to January 1 = *,14)
WRITE(2,200) DECL1(COUNTS(2))
      WRITE(2,200) DECLICONIS(2))
FORMAT (IX, Solar Declination,deg. = ',F6.2)
WRITE(2,300) LONGAS(COUNTS(2))
FORMAT (IX, Longitude of Ascending Node,deg. = ',F6.2)
WRITE(2,310) BASSAN(COUNTS(2))
FORMAT (IX, Right Ascension of the Sun,deg. = ',F6.2)
WRITE(2,340)
DO 400 1=1.365+LEAP
       WRITE(2,350) 1,BETA(1),DECL1(1),RASSUN(1),LONGAS(1)
       FORMAT (3X, 14, 8X, F6.2, 10X, F6.2, 12X, F6.2, 11X, F6.2)
      CONTINUE
       CLOSE (unit=2)
       STOP
       SUBROUTINE SOAP(YEAR, ALT, TLAUNCH, LEAP, MONTHS, DAYS, COLNTS, INCL,
OTIME.BETA, DECLI, LONGAS, RASSUN, IERROR)
Sun-Synchronous Orbit Analysis Program (SOAP)
        written in the form of a FORTRAN SUBROUTINE
        Written by: Brian Killough - NASA Langley Research Center
                                               mail Stop 431
                                               Hampton, VA 23665 (804) 864-7847
        This program calculates all of the necessary orbital parameters
        for a sun-synchronous space experiment. Input for the program includes the year, experiment allifude, and sun-synchronous orbitme. Output for the program includes the BETA angle (angle
         between the sun and the experiment orbit plane) for each day of
        the year, and the maximum and minimum BETA Angles for that year. These maximum and minimum BETA Angles are used to calculate
        orbital parameters such as: Julian Date, Days Relative to January
1, Solar Declination, Orbit Inclination, Longitude of the Ascending
Node, Right Ascension of the Sun, and the Orbit Time. These
parameters can be used to run any radiation analysis program that
        calculates radiation fluxes over one orbit, on a given day.
      VARIABLE DEFINITION:
      YEAR
               # VEAR REQUEST ># 1950
                 = Experiment Altitude
       TLAUNCH = Sun-Synchronous Orbit Time (Hours past midnight)
      LEAP = 1. IF LEAP YEAR; 0. IF NOT LEAP YEAR
MONTHS = MONTH INDICATOR FOR MAX, MIN BETA
      DAYS = DAY INDICATOR FOR MAX, MIN BETA
COUNTS = INDEX INDICATOR FOR MAX, MIN IN ARRAYS
                . inclination angle
      OTIME
                . Orbit time (hours)
                # BETA angle (Angle between the Sun and the Orbit Plane)
      BETA
      DECLI
                * Solar Declination
      LONGAS . Longitude of the Ascending Node
                = Right Ascension of the Su
      FERROR # 0. IF NO ERROR: 1. ERROR IF DATE < 1950 CAL. NOT VALID
    VARIABLES USED IN LOGIC:
      JLDATE = juitan Date
      MLONG = Mean Longitude of the Sun
MANON = Mean Anomaly
      ECLANG . Ecliptic Longitude
               - abliquity of Ecliptic
      OBLEC
      RACREEN = Right Ascension of the Greenwich meridian at midnight
      NAME = Vector Normal to the Experiment (RA-DECL Coord, System)
SUN = Solar Vector (RA-DECL Coord, System)
      DIMENSION BETA(366).DECLI(366).LONGAS(366).RASSUN(366)
DIMENSION COUNTS(2).MONTHS(2).DAYS(2)
    MAXIMUM THEN MINIMUM STORED IN ARRAYS
      INTEGER YEAR LEAP MONTHS DAYS COUNTS LERROR
      REAL ALT TLAUNCH INCL. OTHER
      REAL BETA DECLI LONGAS , RASSUN
      REAL MLONG, MANDW, LESS, INC1, INC2
            PI RAD ARG ECLONG, MALDAY, ILDATE NUMBAY.
            OBLEC, RAS1, RAS2, RACREEN, ANG1, ANG2, XHORM1, XHORM2, XHORM3,
             XSLN. VSLN. ZSLN. XNSLN. BETAMAX. BETAMIN
      INTEGER COUNT, COUNT1, COUNT2, 1, NF IRST, NLAST
      INTEGER DAYONT(13)
```

```
DATA DAYONT/0,31,59,96,120,151,181,212,243,273,304,334,366/
   DEFINE ILLDAT . 12:00 NOON IAN. 1, 1950
     DATA JULDAT/2433282.5/
FORMAT(/, IX, "******* PLEASE WAIT - PROCESSING *********./)
     P1=3.14159265359
     LESSHO.
     LEAP+0
     RAD=180./PI
   CHECK YEAR REQUEST
      IERROR = 0
     IF(YEAR.LT.1950) THEN
PRINT *," YEAR REQUEST LESS THAN 1950 ... CANNOT ",
"CALCULATE"
       IERROR = 1
       GO TO 200
       ENDIF
CALCULATE INCLINATION ANGLE AND TIME
        INC1= RAD*ACOS(0.9856473*(6378.145+ALT)**3.5
             /(-2064.5874E+11))
        INC2= 1+(66058.33/((ALT+6378.145)**2))*(1-1.5*(SIN(INC1
              /RAD) **2))
        INCL = RAD*ACOS((COS(INC1/RAD))/INC2)
     OTIME=0.0
     IF ((INCL.LT.97.641).AND.(INCL.GE.96.566)) OTIME=
         24/((INCL-97.641)/(96.566-97.641)+15)
     IF ((INCL.LT.98.988), AND. (INCL.GE.97.641)) OTIME=
         24/{(INCL-98.988)/(97.641-98.988)+14)
     IF ((INCL.LT.100.706).AND.(INCL.GE.98.988)) OTIME=
24/((INCL-100.706)/(98.988-100.706)+13)
     IF ((INCL.LE.102.944).AND.(INCL.GE.100.706)) OTIME=
        24/{(INCL=102.944)/(100.706-102.944)+12}
* CALCULATE JULIAN DATE FROM JAN 1 1950
     NLMDAY = (YEAR-1950)*365. + JULDAT + INT(FLOAT(YEAR-1950.)/4.
               +0.49)
     IF (MOD((YEAR-1950).4).EQ.2) LEAP=1
  ORBITAL PARAMETER CALCULATION .
     DO 150 COLNT=1.365+LEAP
        JLDATE = COUNT + NUMBAY
         ARG= -4018.5 + COUNT
     MLONG= 280.460+0.9856474*ARG+LESS*360.
IF (MLONG.GT.0.0) GOTO 20
        LESS=LESS+1.
        COTO 10
     LESS=0.
        #ANON# 357.528+0.9856003*ARG+LESS*360.
     IF (MANON.GT.0.0) GOTO 40
        LESSeLESS+1
        COTO 30
40 IF55+0.
        ECLONG= MLONG+1.915*SIN(MANOM/RAD)+0.02*SIN(2*MANOM/RAD)
        OBLEC= 23.439-0.0000004*ARG
DECLI(COUNT)= RAD*ASIN(SIN(ECLONG/RAD)*SIN(OBLEC/RAD))
        RAS1= ( JLDATE-2415020.0)/36525*36000.7689
        RAS2= 0.00038708*(( JLDATE-2415020.0)/36525)**2
50
        RAGREEN# 99.6909833+RAS1+RAS2-LESS*360.
           IF (RACREEN.LT.360.0) COTO 60
              LESS=LESS+1.
              COTO 50
        1 555-0
        LONGAS(COUNT) = RAGREEN+TLAUNCH+60.40.25068447-LESS+360.
70
           IF (LONGAS(COUNT).LT.360.0) GOTO 80
              LESS=LESS+1.
              COTO 70
80
        LESS#O
         RASSUN(COUNT) = RAD*ATAN(COS(OBLEC/RAD)*TAN(ECLONG/RAD)}
        IF ((RASSUN(COUNT).GT.0.0).AND.(RASSUN(COUNT).LT.360.0))
             COTO 130
         IF (RASSUN(COUNT) .GT. 360.0) COTO 100
         IF (RASSUN(COUNT).LT.0.0) RASSUN(COUNT)=RASSUN(COUNT)+
                                               LESS*360.
           LESS=LESS+1.
           COTO 90
        LESS=1.
 100
        RASSUN(COUNT)=RASSUN(COUNT)-LESS*360.
 120
        LESS=LESS+1.
         IF (BASSLN(COLNT), CT. 360.0) COTO 120
        ANG 1 = ECL ONG
 110
        ANG2=RASSUN(COLNT)
         IF ((ANG1.GE.0.0), AND. (ANG1.LT.90.0)) THEN
            IF ((ANG2,GE.0.0),AND.(ANG2,LT.90.0)) GOTO 140
```

```
IF ((ANC2.GE.90.0), AND. (ANC2.LT.180.0)) ANC2-ANC2-90.
             IF ((ANG2.GE.180.0).AND.(ANG2.LT.270.0)) ANG2=ANG2-180.
              ANG2=ANG2-270.
          FADIF
          IF ((ANG1.GE.98.0).AND.(ANG1.LT.180.0)) THEN
IF ((ANG2.GE.0.0).AND.(ANG2.LT.90.0)) ANG2=ANG2+90.
              IF ((ANG2.GE.90.0).AND.(ANG2.LT.180.)) COTO 140
             IF ((ANG2.GE.180.0).AND.(ANG2.LT.270.)) ANG2=ANG2-90.
             ANG2=ANG2-180.
          ENDIF
          IF ({ANG1.GE.180.}.AND.(ANG1.LT.270.}) THEN
             IF ((ANG2.GE.0.0).AND.(ANG2.LT.90.0)) ANG2=ANG2+180.
IF ((ANG2.GE.90.0).AND.(ANG2.LT.180.0)) ANG2=ANG2+90.
             IF ((ANG2.GE.180.0).AND.(ANG2.LT.270.0)) GOTO 140
             ANG2=ANG2-90
          ENDIF
          IF ((ANG1.GE.270).AND.(ANG1.LT.360.)) THEN
             IF ((ANG2.GE.0.0).AND.(ANG2.LT.90.0)) ANG2=ANG2+270.
             IF ((ANG2.GE.90.0).AND.(ANG2.LT.180.0)) ANG2=ANG2+180.
             IF ((ANG2.GE.180.0).AND.(ANG2.LT.270.0)) ANG2=ANG2+90.
 140 RASSUN(COUNT) = ANG2
     BETA ANGLE CALCULATION
      XNORM1=SIN(INCL/RAD)*SIN(LONGAS(COUNT)/RAD)
       XNORM2=-SIN(INCL/RAD) *COS(LONGAS(COUNT)/RAD)
      XNORM3=COS (INCL /RAD)
       XSUN=COS (ECLONG/RAD)
      YSUN=SIN(ECLONG/RAD) *COS(OBLEC/RAD)
      ZSLN=SIN(ECLONG/RAD) *SIN(OBLEC/RAD)
       XNSUN=RAD*ACOS (XNORM 1 *XSUN+XNORM 2 *YSUN+XNORM 3 *ZSUN)
      BETA(COUNT)=ABS(90-XNSUN)
 150 CONTINUE
*****************************
* MAXIMUM + MINIMUM BETA ANGLES *
      BETAMAX=BETA(1)
      BETAMIN=BETA(1)
      DO 160 1=2.365+LEAP
         IF (BETAMIN.GT.BETA(1)) THEN
            COUNT 2 = 1
            BETAMIN=BETA(1)
         ENDIF
         IF (BETAMAX.LT.BETA(I)) THEN
            COUNT 1= i
            BETAMAX=BETA(1)
         ENDIF
 160 CONTINUE
*****************************
   FIND DATE OF MAX AND MIN
     NFIRST = DAYCNT(1)
      00 170 1=1,12
      NLAST = DAYONT(1+1)
      IF(1.GT.1) THEN
        NLAST = NLAST + LEAP
        ENDIF
      IF(COUNT).GT.NFIRST .AND. COUNT) LE.NLAST) THEN
        COUNTS(1) = COUNT1
        DAYS(1) = COUNT1 - NEIRST
        MONTHS(1) m I
        ENDIF
      IF(COUNT2.GT,NFIRST .AND. COUNT2.LE.NLAST) THEN
        COUNTS(2) = COUNT2
        DAYS(2) = COUNT2 - NEIRST
        MONTHS(2) = 1
        ENDIF
     NEIRST . NEAST
 170 CONTINUE
 200 CONTINUE
     RETURN
     END
```

ORIGINAL PAGE IS OF POOR QUALITY

Appendix B SOAP Example Output

> Year of Launch = 1998 Altitude (km) = 705.0

Sun-Synchronous Orbit Time - 13.50

Orbit Inclination Angle, deg. - 98.21 Orbit Time (hours) - 1.65

Maximum Beta Angle, deg. = 29.04 Date of Maximum Beta Angle = 11/5

Days Relative to January 1 - 309

Solar Declination, deg. = -15.60

Longitude of Ascending Node, deg. - 248.07

Right Ascension of the Sun, deg. - 220.10

Minimum Beta Angle, deg. - 17.28

Date of Minimum Beta Angle - 7/9

Days Relative to January 1 - 190

Solar Declination, deg. = 22.39

Longitude of Ascending Node, deg. - 130.77

Right Ascension of the Sun, deg. = 108.19

Day of Year	Beta Angle	Solar Declination	Right Ascension of the Sun	Longitude of Ascending Node
1	24.33	-23.02	281.47	304.48
2	24.22	-22.94	282.58	305.47
3	24.12	- 22 . 84	283.68	306.46
4	24.01	-22.75	284.78	307.44
5	23.91	-22.64	285,88	308.43
6	23.81	-22.52	286,98	309.41
7	23.71	-22.40	288.07	310.40
8	23.61	-22.27	289.16	311.39
9	23.52	-22.14	290.25	312.37
10	23.42	-21.99	291.34	313.36
•	•	•	•	•
•	•	•	Ÿ	•
•	•	•	•	•
	•	÷ ±	•	··· *
358	25.24	-23.42	272.34	296.36
359	25.13	-23.40	273.45	297.35
360	25.02	-23.37	274.56	298.33
361	24.91	-23.34	275.67	299.32
362	24.79	-23.29	276.78	300.30
363	24.68	-23.24	277.89	301.29
364	24.57	-23.18	279.00	302.28
365	24.46	-23.12	280.10	303.26

APPENDIX C

Input and Output Calling Arguments for the SOAP Subroutine

SOAP has been written in FORTRAN in the form of a subroutine, designed to be called from any other computer code. The input and output calling arguments are described below in detail.

USE: CALL SOAP (YEAR, ALT, TLAUNCH, LEAP, MONTHS, DAYS, COUNTS, INCL, OTIME, BETA, DECLI, LONGAS, RASSUN, IERROR)

INPUT: YEAR An input integer, designating the year, must be \geq 1950.

ALT An input real variable, experiment altitude, km.

TLAUNCH An input real variable, Sun-synchronous Orbit time (hours past midnight). i.e. 13.5 (= 1:30 pm ascending node)

OUTPUT: LEAP Output integer variable, = 0, YEAR is not a leap year; = 1, YEAR is a leap year.

MONTHS Output integer array, dimensioned 2, containing the month indicator for maximum followed by the minimum BETA occurrence.

DAYS Output integer array, dimensioned 2, containing the day indicator of the value MONTHS for the maximum followed by the minimum BETA occurrence.

COUNTS Output integer array, dimensioned 2, containing the index pointers in the BETA, DECLI, LONGAS, RASSUN arrays for the maximum followed by the minimum BETA occurrence.

INCL Output real variable, the inclination angle, deg.

OTIME Output real variable, Orbit time, hours.

BETA Output real array, dimensioned 366, angle between the Sun and the Orbit Plane, deg.

DECLI Output real array, dimensioned 366, solar declination angle, deg.

LONGAS Output real array, dimensioned 366, longitude of the ascending node, deg.

RASSUN Output real array, dimensioned 366, right Ascension of the Sun, deg.

IERROR Output integer, = 0, if no error; = 1, error if YEAR < 1950.

APPENDIX D

Governing Equations for the Calculation of Orbital Parameters

Assuming a fictitious spherical Earth and a nearly circular orbit, the altitude of the spacecraft can be expressed as

$$a = h + 6378.145$$
 (D1)

where a is the altitude above the center of the Earth and h is the nominal altitude of the satellite above the Earth's surface in kilometers. Using an iterative approach, the orbit inclination can be found from the following equations (ref. 4)

$$c1 = cos^{-1} (0.9856473 a^{3.5} / -2.0645874 x 10^{14})$$
 (D2)

$$c2 = 1 + 66058.33 (1 - 1.5 sin^2 (c1)) / a2$$
 (D3)

$$i - \cos^{-1}(\cos(c1) / c2)$$
 (D4)

where i is the orbit inclination in degrees. Equations (D1) and (D2) are iterative steps used to calculate the orbit inclination.

The following equations used to calculate orbital parameters give the apparent coordinates of the Sun to a precision of 0.01 degrees and time to a precision of 0.1 minutes. Similar equations can be found in references 3 and 6. As expected, the location of the Sun is dependent on the day of the year. Thus a time argument is used to calculate the Sun's location in a right ascension - declination coordinate system. The time argument is expressed as (ref. 5)

$$n = -4018.5 + d (D5)$$

where d is the day of the year. The time argument is used to calculate several orbital angles

$$L = 280.460 + 0.9856474 n$$
 (D6)

$$g = 357.528 + 0.9856003 n$$
 (D7)

$$\lambda = L + 1.915 \sin g + 0.02 \sin 2g$$
 (D8)

$$\epsilon = 23.439 - 0.0000004 n$$
 (D9)

where L is the mean longitude of the Sun, g is the mean anomaly, λ is the ecliptic longitude, and ϵ is the obliquity of the Earth's equator to the ecliptic, in degrees. These equations are used to calculate the right ascension of the Sun (D10), and the solar declination (D11).

$$S = \sin^{-1} (\sin \epsilon \sin \lambda)$$
 (D11)

In equations (D6) through (D11), and other equations involving angular results in degrees, the results often produce angles not within the customary range of

O to 360 degrees. Therefore, all angles should be converted to values within this range. Using the results from equations (D8) and (D9) the Sun's position, normalized with respect to the distance from the Sun to the Earth, can be expressed as a vector with rectangular coordinates.

$$X_s = \cos \lambda$$
 (D12)

$$Y_s = \cos \epsilon \sin \lambda$$
 (D13)

$$Z_{s} = \sin \epsilon \sin \lambda$$
 (D14)

The solar vector in the right ascension - declination coordinate system is

$$\hat{S} = X_S \hat{i} + Y_S \hat{j} + Z_S \hat{k}$$
 (D15)

The spacecraft position can be expressed in a similar manner using equations dependent on the day of the year, sun-synchronous orbit time, and the inclination angle. The time argument for these equations is (ref. 4)

$$T = (J - 2415020) / 36525$$
 (D16)

where T is the time in Julian centuries from the date January 0.5, 1900 and J is the Julian date. The right ascension of the Greenwich meridian at midnight can be expressed as

$$r = 99.6909833 + 36000.7689 T + 0.00038708 T^2$$
 (D17)

with the result falling between 0 and 360 degrees. The equation for longitude of ascending node is

$$\Lambda = r + 15.0410682 t$$
 (D18)

where t is the sun-synchronous orbit time in hours past midnight. Equations (D4) and (D18) can be used to calculate the spacecraft position in rectangular coordinates for a right ascension - declination coordinate system. These coordinates are

$$X_n = \sin i \sin \Delta$$
 (D19)

$$Y_n = -\sin i \cos \Delta \qquad (D20)$$

$$Z_n = \cos i$$
 (D21)

and the corresponding vector equation

$$\hat{N} = X_n \hat{i} + Y_n \hat{j} + Z_n \hat{k}$$
 (D22)

The angle between the orbit plane of the spacecraft and the solar vector can be found by taking the dot product of the two vectors in equations (D15) and (D22). This result yields the "Beta Angle", in degrees, which is one of the most important parameters for spacecraft thermal analysis.

$$\beta = 90 - \cos^{-1} \left(\hat{S} \cdot \hat{N} \right)$$
 (D23)

REFERENCES

- 1. Brooks, David R.: An Introduction to Orbit Dynamics and its Applications to Satellite Based Earth Monitoring Missions, NASA Reference Publication 1009, November 1977.
- 2. Harrison, Edwin F.; Brooks, David R.; and Gibson, Gary G.: Mission Analysis to Define Satellite Orbits for Earth Radiation Budget Measurements. AIAA Paper 76-811, August 1976.
- 3. Anon: TRASYS, Thermal Radiation Analyzer System, Users Manual, NASA Lyndon B. Johnson Space Center, December 1987.
- 4. Explanatory Supplement to the Astronomical Ephemeris and the American Ephemeris and Nautical Almanac, H.M. Nautical Almanac Office, 1961.
- 5. Anon: The America Ephemeris and Nautical Almanac, U.S. Naval Observatory, 1967.

ace Administration	2. Government Accession No	3. Recipient's Catalog No.
leport No.	2. Government Accession No.	d. Neeplan a catalog (ve.
NASA TM-101630		
itle and Subtitle		5. Report Date
Thermal and Orbita	1 Analysis of Earth	May 1990
Monitoring Sun-Syn Experiments		6. Performing Organization Code
uthor(s)		8. Performing Organization Report N
Brian D. Killough		
DI 1411 D. 111110-6.		10. Work Unit No.
		413-18-06-10
erforming Organization Name	and Address	11 Control of Cont No.
NASA Langley Resea	arch Center	11. Contract or Grant No.
Hampton, VA 23665		
		13. Type of Report and Period Covere
ponsoring Agency Name and	Address	Technical Memorandu
National Aeronauti Washington, DC 20	ics and Space Administration 0546	14. Sponsoring Agency Code
The fundamentals of A Sun-synchronous calculate orbital provides the required, which in turnincident on a space input to a general instrument operation the thermal and	of an Earth monitoring Sun-synch Orbit Analysis Program (SOAP) he parameters for an entire year. Ired input data for the TRASYS to the computes the infrared, solar the experiment. Direct incident lized thermal analyzer program to ling temperatures. The SOAP companysis methodology presented in	as been developed to The output from this programmed radiation computer and Earth albedo heat fluxe heat fluxes can be used as o size radiators and predicuter code and its application this paper, should prove
The fundamentals of A Sun-synchronous calculate orbital provides the requicode, which in turincident on a space input to a general instrument operation the thermal and useful to the thermal sun-synchronous space.	Orbit Analysis Program (SOAP) he parameters for an entire year. Ired input data for the TRASYS to computes the infrared, solar ce experiment. Direct incident lized thermal analyzer program to the temperatures. The SOAP compalysis methodology presented in the mal engineer during the design pace experiments.	as been developed to The output from this programmer radiation computer and Earth albedo heat fluxe heat fluxes can be used as o size radiators and predicuter code and its application this paper, should prove phases of Earth monitoring
A Sun-synchronous calculate orbital provides the required, which in turnincident on a space input to a general instrument operation the thermal and useful to the them.	Orbit Analysis Program (SOAP) It parameters for an entire year. Itred input data for the TRASYS to computes the infrared, solar ce experiment. Direct incident lized thermal analyzer program to the temperatures. The SOAP compalysis methodology presented in small engineer during the design pace experiments.	as been developed to The output from this programmer radiation computer and Earth albedo heat fluxe heat fluxes can be used as o size radiators and predicuter code and its application this paper, should prove phases of Earth monitoring
The fundamentals of A Sun-synchronous calculate orbital provides the required, which in turnincident on a space input to a general instrument operation the thermal and useful to the themal and useful to the themal of the themal and useful to the themal sun-synchronous space.	Orbit Analysis Program (SOAP) is parameters for an entire year. Ired input data for the TRASYS to computes the infrared, solar ce experiment. Direct incident lized thermal analyzer program to the temperatures. The SOAP compalysis methodology presented in small engineer during the design pace experiments.	as been developed to The output from this programmer and radiation computer and Earth albedo heat fluxes heat fluxes can be used as o size radiators and predicuter code and its application this paper, should prove phases of Earth monitoring

Unclassified

•			
•			
•			
•			